

UM220-IV L

Multi-GNSS Single-frequency Timing Module



 Industrial Grade

17.0 × 22.4 × 2.4 mm



Product Characteristics

- » Multi-mode single-frequency timing, with the timing accuracy better than 20ns
- » Supports GPS + BDS/GLONASS + Galileo, as well as BDS-3 constellation
- » Supports single satellite timing, ensuring high reliability even if there is only one visible satellite
- » Supports antenna open circuit warning and short circuit protection
- » Compatible with mainstream GPS timing modules and saving cost

Applications

-  Telecom Base Station Timing
-  Electrical Power Grid Timing
-  Network Time Synchronization

Brief Introduction

UM220-IV L is a timing module developed for telecom timing and electrical power grid timing, supporting GPS, BDS, GLONASS, and Galileo. The module is based on Unicore's proprietary low-power SoC-UFirebird UC6226, and supports multi-mode timing. It features high accuracy, high stability, high reliability, and is suitable for large-scale GNSS timing applications.

15	GND	GND	14
16	RF_IN	GND	13
17	GND	NC	12
18	VCC_RF	V_BCKP	11
19	V_ANT	nRESET	10
20	ANT_DET_N	NC	9
UM220-IV L			
21	NC	VCC_OUT	8
22	NC	GND	7
23	NC	VCC	6
24	NC	NC	5
25	NC	RXD1	4
26	NC	TXD1	3
27	NC	RXD2	2
28	TIMEPULSE	TXD2	1

Ordering Information

Supply at multiples of 500 pieces

Physical Specifications

Dimensions	17.0 × 22.4 × 2.4 mm
Weight	1.7 g
Package	28 pin SMD
Operating Temperature	-40°C ~ +85°C
Storage Temperature	-40°C ~ +85°C

Electrical Specifications

Voltage	3.0 V ~ 3.6 V DC
LNA	3.0 V ~ 3.3 V, < 100 mA
Power Consumption ²	62 mW @3.3V

Interfaces

- 2 × UART
- 1 × 1PPS

Functional Characteristics

- Passive antenna, active antenna
- Single satellite timing mode

Note: The parts marked with * are supported by specific firmware.
 1 Typical value, < 30 m/s open sky
 2 Open sky, continuous tracking

Performance Specifications

Channel	64 channels, based on UFirebird
	GPS L1C/A
	BDS B1I
Frequency	GLONASS G1
	Galileo E1
Modes	Single-System Standalone Positioning
	Multi-System Joint Positioning
Positioning Accuracy (CEP) ¹	Horizontal: 2.0 m
	Vertical: 3.5 m
1PPS	Better than 20 ns (1σ)
	Cold Start < 30 s
Time to First Fix (TTFF)	Hot Start < 1 s
	Reacquisition < 1 s
Sensitivity	GNSS
	Tracking -160 dBm
	Cold Start -147 dBm
	Hot Start -155 dBm
	Reacquisition -155 dBm
Data Update Rate	1 Hz
Data Format	NMEA 0183, Unicore