

# UB482

GPS/BDS/GLONASS/Galileo  
All-constellation Multi-frequency High  
Precision Heading Board



46 × 71 × 10mm

## Product Characteristics

- » Based on multi-system multi-frequency high performance SoC - NebulasII, with 432 super channels
- » Support BDS, GPS, GLONASS, Galileo and QZSS, including Beidou-3 signal
- » Support dual-antenna signal input, capable of positioning and heading with only one single board
- » Simultaneous output of positioning and heading data at the rate of more than 20 Hz
- » Re-acquisition time of RTK within 1s
- » Support serial port, Ethernet port, 1PPS, Event and other physical interfaces; support hot start\*
- » 46x71mm compact board, compatible with other mainstream boards

## Applications



Driving Test



Precision  
Agriculture



Mechanical  
Control

## Brief Introduction

UB482 is a new generation positioning and heading board developed by Unicore Communications and is based on the high-performance high-precision SoC - NebulasII. It supports BDS B1I/B2I, GPS L1/L2, GLONASS L1/L2, Galileo E1/E5b, and QZSS L1/L2. UB482 adopts classic compact design and supports network data transmission. It is widely used in agricultural machinery, driving tests and intelligent driving.

## Electrical Specifications

Voltage	3V~5V DC
LNA	4.75~5.10V, 0~100 mA
Ripple Voltage	100mVp-p (max)
Power Consumption	2.4 W (Typical)

## Physical Specifications

Dimensions	46 × 71 × 10mm
Weight	21 g
I/O Connectors	2 x 14 pin
Antenna Input	2 x MMCX

## Functional Ports

3 x UART (LV-TTL)	1 x Event
1 x 1 PPS (LV-TTL)	1 x LAN

## Environmental Specifications

Temperature	Working: -40 °C~+85 °C Storage: -55 °C~+95 °C
Humidity	95% No condensation
Vibration	GJB150.16-2009,MIL-STD-810
Shock	GJB150.18-2009,MIL-STD-810

NOTE: The parts marked with \* are optional configurations;  
BDS B1I/B3I can be supported by firmware upgrade.

## Performance Specifications

Channel	432 channels, based on Nebulas-II UC4C0 chip			
Frequency	BDS B1I/B2I GPS L1/L2 GLONASS L1/L2 Galileo E1/E5b QZSS L1/L2			
Single Point Positioning(RMS)	Horizontal: 1.5m	Vertical: 2.5m		
DGPS(RMS)	Horizontal: 0.4 m	Vertical: 0.8 m		
RTK(RMS)	Horizontal: 0.8cm + 1ppm	Vertical: 1.5cm + 1ppm		
Cold Start	<25s	Data Output	NMEA-0183, Unicore	
Hot Start	<10s	Correction	RTCM v3.0/3.2	
RTK Initialization Time	<5s (Typical)	Reacquisition	< 1 s	
Initialization Reliability	>99.9%	Observation Update Rate	20Hz*	
Heading Accuracy	0.2 degree/ 1m baseline	Location Update Rate	20Hz*	
Velocity Accuracy(RMS)	0.03 m/s	Network Protocol	NTRIP, TCP/IP	
Time Accuracy(RMS)	20 ns			
Observation Accuracy	BDS	GPS	GLONASS	Galileo
B1/L1 C/A/G1/E1 Code	10cm	10cm	10cm	10cm
B1/L1/G1/E1 Carrier Phase	1mm	1mm	1mm	1mm
B2/L2P(Y)/L2C/G2/E5b Code	10cm	10cm	10cm	10cm
B2/L2P(Y)/L2C/G2/E5b Carrier Phase	1mm	1mm	1mm	1mm